

Amendments to the Claims

Please cancel Claims 23, 28-43 and 54-59 without prejudice to or disclaimer of the subject matter recited therein.

Please amend Claims 1, 8, 14, 16, 44 and 49 to read as follows.

1. (Currently amended) A carbonation system comprising:  
a vessel for carbonating a liquid, the longitudinal axis of said vessel being in  
~~the a~~ horizontal plane;  
a CO<sub>2</sub> supply connected to said vessel so as to create a CO<sub>2</sub> atmosphere in  
said vessel;  
an inlet diffuser through which the liquid enters said vessel, said inlet  
diffuser comprising a plurality of openings arranged on a vertical face, wherein the  
plurality of openings are oriented such that when the liquid exits said inlet diffuser through  
the plurality of openings, the liquid is substantially atomized and substantially all of the  
atomized liquid is ejected in a direction that is substantially in ~~the a~~ horizontal plane; and  
an outlet pipe through which the carbonated liquid exits said vessel.
  
2. (Original) A carbonation system according to claim 1, wherein the  
plurality of openings are holes.

3. (Withdrawn) A carbonation system according to claim 2, wherein the diameters of the holes are approximately 0.016-0.036 inches.

Claims 4 and 5 (cancelled)

6. (Original) A carbonation system according to claim 1, wherein the inlet liquid pressure is approximately 100 to 140 psi.

7. (Original) A carbonation system according to claim 1, wherein said inlet diffuser is positioned in the approximate longitudinal center of said vessel.

8. (Currently amended) A carbonation system according to claim 1, wherein wherein said vessel is cylindrical in shape.

9. (Original) A carbonation system according to claim 1, wherein the plurality of openings are arranged in a plurality of horizontal rows.

10. (Original) A carbonation system according to claim 1, wherein the plurality of openings are oriented to eject the atomized liquid substantially along the longitudinal axis of said vessel.

11. (Original) A carbonation system according to claim 1, wherein said vessel comprises end walls at either longitudinal end and the plurality of openings are oriented to eject the atomized liquid toward the end walls of said vessel.

12. (Original) A carbonation system according to claim 1, wherein said vessel comprises side walls and end walls at either longitudinal end of said side walls, and the plurality of openings are oriented such that the atomized liquid is not ejected toward the side walls of said vessel.

13. (Original) A carbonation system according to claim 1, wherein said vessel comprises side walls and end walls at either longitudinal end of said side walls, and the plurality of openings are oriented such that the atomized liquid is not ejected toward a central region of the side walls of said vessel.

14. (Currently amended) A carbonation system comprising:  
a vessel for carbonating a liquid, the longitudinal axis of said vessel being in a horizontal plane;

a CO<sub>2</sub> supply connected to said vessel so as to create a CO<sub>2</sub> atmosphere in said vessel;

an inlet diffuser through which the liquid enters said vessel, said inlet diffuser comprising a plurality of openings arranged on a vertical face, wherein the plurality of openings are oriented such that when the liquid exits said inlet diffuser through

the plurality of openings, the liquid is substantially atomized and wherein the plurality of openings are arranged in horizontal rows such that openings in adjacent rows of the plurality of openings are not in vertical alignment with each other, and wherein substantially all of the atomized liquid is ejected in directions that are substantially in horizontal planes; and

an outlet pipe through which the carbonated liquid exits said vessel.

15. (Original) A carbonation system according to claim 14, wherein adjacent rows of the plurality of openings have a different number of openings per row.

16. (Currently amended) A carbonation system according to claim 14, wherein the inlet liquid pressure is approximately 100 to 140 psi.

17. (Original) A carbonation system according to claim 14, wherein the plurality of openings are holes.

18. (Original) A carbonation system according to claim 17, wherein the diameters of the holes are approximately 0.020-0.036 inches.

Claims 19 and 20 (cancelled)

21. (Original) A carbonation system according to claim 14, wherein said inlet diffuser is positioned in the middle of said vessel.

22. (Original) A carbonation system according to claim 14, wherein said vessel is cylindrical in shape.

Claim 23 (cancelled)

24. (Original) A carbonation system according to claim 14, wherein the plurality of openings are oriented to eject the atomized liquid substantially along the longitudinal axis of said vessel.

25. (Original) A carbonation system according to claim 14, wherein said vessel comprises end walls at either longitudinal end and the plurality of openings are oriented to eject the atomized liquid toward the end walls of said vessel.

26. (Original) A carbonation system according to claim 14, wherein said vessel comprises side walls and end walls at either longitudinal end of said side walls, and the plurality of openings are oriented such that the atomized liquid is not ejected toward the side walls of said vessel.

27. (Original) A carbonation system according to claim 14, wherein said vessel comprises side walls and end walls at either longitudinal end of said side walls, and the plurality of openings are oriented such that the atomized liquid is not ejected toward a central region of the side walls of said vessel.

Claims 28-43 (cancelled)

44. (Currently amended) A method for carbonating a liquid comprising the steps of:

providing a vessel for carbonating a liquid, where the longitudinal axis of the vessel is in the a horizontal plane;

supplying a CO<sub>2</sub> atmosphere in the vessel;

pumping the liquid into an inlet diffuser to atomize the liquid and eject substantially all of the atomized liquid into the vessel in a direction that is substantially in the a horizontal plane by forcing the liquid through a plurality of openings arranged on a vertical face of the diffuser; and

discharging the carbonated liquid out of the vessel.

45. (Original) A method according to claim 44, wherein the atomized liquid is ejected substantially along the longitudinal axis of the vessel.

46. (Original) A method according to claim 44, wherein the vessel comprises end walls at either longitudinal end, and the atomized liquid is ejected toward the end walls of the vessel.

47. (Original) A method according to claim 44, wherein the vessel comprises side walls and end walls at either longitudinal end of the side walls, and the atomized liquid is not ejected toward the side walls of the vessel.

48. (Original) A method according to claim 44, wherein the vessel comprises side walls and end walls at either longitudinal end of the side walls, and the atomized liquid is not ejected toward a central region of the side walls of the vessel.

49. (Currently amended) A method for carbonating a liquid comprising the steps of:

providing a vessel for carbonating a liquid, the longitudinal axis of the vessel being in a horizontal plane;  
supplying a CO<sub>2</sub> atmosphere in the vessel;  
atomizing the liquid and ejecting the atomized liquid into the vessel through a plurality of openings arranged on a vertical face of an inlet diffuser, wherein the plurality of openings are arranged in horizontal rows such that openings in adjacent rows of the plurality of openings are not in vertical alignment with each other, wherein substantially all

of the atomized liquid is ejected in directions that are substantially in horizontal planes;

and

discharging the carbonated liquid out of the vessel.

50. (Original) A method according to claim 49, wherein the atomized liquid is ejected substantially along the longitudinal axis of the vessel.

51. (Original) A method according to claim 49, wherein the vessel comprises end walls at either longitudinal end, and the atomized liquid is ejected toward the end walls of the vessel.

52. (Original) A method according to claim 49, wherein the vessel comprises side walls and end walls at either longitudinal end of the side walls, and the atomized liquid is not ejected toward the side walls of the vessel.

53. (Original) A method according to claim 49, wherein the vessel comprises side walls and end walls at either longitudinal end of the side walls, and the atomized liquid is not ejected toward a central region of the side walls of the vessel.

Claims 54-59 (cancelled)